

757 BVE Series Blanking Plugs

Increased Safety

Cable Gland Accessories.

NEC/CEC:
 Class I, Groups A,B,C,D
 Class II, Groups E,F,G
 Class III
 Ex e II, Class I, Zone 1
 AEx e II; IP66, 67, 68

ATEX/IECEX:
 Zone 1 and 2 – 21 and 22
 Ⓢ II 2 GD
 IP66

Applications

- A comprehensive range of plastic blanking plugs designed to close any unused entries in electrical equipment.
- Entry thread sealing washer supplied.

Features

- Catering to hazardous areas, the range covers all metric threads from M16 to M50.
- Certification Ex e.

Standard Materials

- Nylon

NEC/CEC Certifications and Compliances

- UL Standard: 886 (1203), E60079-0, E60079-1, E60079-7
- CSA Standard: C22.2 No. 30, CAN/CSA E60079-0, CAN/CSA E60079-1, CAN/CSA E60079-7
- cCSAus Certified: 113642

ATEX/IECEX Certifications and Compliances


- Certification Type BVe
 - Gas: Zones 1 and 2
 - Type of Protection: Ex e II
- Dust: Zone 21 and 22
 - Type of Protection: Ex tD
- Conforming to ATEX 94/9/CE: Ⓢ II 2GD
- Ambient Temperature: -40 °C to +55 °C (-40 °F to +131 °F)
- CE Declaration of Conformity: 5C218
- ATEX Certificate: LCIE 03 ATEX 0011U
- IECEX Certificate: IECEX LCI 04.0027U
- Index of Protection according EN/IEC 60529: IP66

INMETRO Certification

- INMETRO Certificate: BVC 11.0600-U



Dimensions in Millimeters (Inches)



| Dimensions mm (in) B | Metric | Weight kg (lbs) | Volume dm ³ (in ³) | Catalog Number |
|-------------------------|--------|--------------------|--|----------------|
| – | M16 | 0.10 (0.22) | 0.03 (1.83) | 095485 |
| 12.0 (0.47) | M20 | 0.10 (0.22) | 0.03 (1.83) | 095714 |
| 12.0 (0.47) | M25 | 0.10 (0.22) | 0.03 (1.83) | 095715 |
| 12.0 (0.47) | M32 | 0.10 (0.22) | 0.03 (1.83) | 095486 |
| 12.0 (0.47) | M40 | 0.10 (0.22) | 0.07 (4.27) | 095487 |
| – | M50 | 0.20 (0.44) | 0.07 (4.27) | 095488 |