

Enzyme Treatment Panzym® Extract G



Pectinolytic Enzyme Maceration Preparation for Winemaking - Free from Cinnamylesterase (Depsidase)

Panzym Extract G enzyme from Eaton's Begerow Product Line is a granulated enzyme preparation that is produced from a selected strain of *Aspergillus niger* by means of submerged fermentation. Undesired cinnamylesterase activity (CE) and colorants are removed in a special cleaning step to thus produce a nearly white finished enzyme preparation. Panzym Extract G enzyme is a highly concentrated pectinolytic preparation, activities that selectively degrade grape skin polysaccharides in the grape mash.

Application

Panzym Extract G enzyme was developed for treatment of white and red grape mashes for the purpose of quality improvement. The selective degradation of grape skins facilitates release of the juice during pressing and makes it possible to **gently extract valuable aroma, aroma precursors, and desired phenols (tannins). Decreased quantities of aggressive tannin and stabilized colorants are extracted from the red mash.** Depectinization and a decrease of viscosity is additionally achieved during the clarification process. The active enzyme components contained in Panzym Extract G enzyme are easily dissolved in must or water using concentrations occurring under normal working conditions. The product is added as a 10% solution directly into the mash wagon, crushing mill, press, or to the grape mash tank prior to filling. Even distribution of the enzyme in the mash is ensured by pumping.

Activity

Panzym Extract G enzyme has an activity of activity of 13,275 PGNU/dr (7,500 PGNU/g) at 68 °F (20 °C). It is clean and free of cinnamylesterase.

Dosage

Area of application	Dosage lb/1,000gal (g/hl)	Period h
Maceration of white grapes (release of juice, aroma, and aroma precursors)	0.17 – 0.25 (2 – 3)	2 – 4
Maceration of red grapes (extraction of colorants and tannin, polysaccharides, and aroma)	0.25 – 0.33 (3 – 4)	6 – 12

Special Notes

Enzymes are irreversibly destroyed when brought in contact with bentonite.

The enzymatization reaction must be completed prior to using bentonite or the bentonite must have been removed prior to enzymatization.

Any necessary bentonite treatment should be performed after the enzyme treatment, otherwise the enzyme will be absorbed by the bentonite and thus rendered ineffective.

The application of up to 0.42 lb/1,000 gal (50 mg/l) of SO₂ has no effect on the enzyme activity.

Safety and Purity

This product is a white, soluble micro-granulate without preservatives and virtually free of dust. It complies with FAO/WHO JEFCA and FCC guidelines for food enzymes.

Further safety information can be found in the relevant Material Safety Data Sheet, which can be downloaded from our website.

Storage

Panzym Extract G enzyme is a micro-granulate and is thus exceptionally resistant. When stored at a temperature of max. 77 °F (25 °C) it will retain its indicated activity for many years.

The product should be stored in a dry place to avoid the formation of rust on the cans.

Delivery Information

Panzym Extract G enzyme is sold under article no. 95.122.001 and is available in the following package size:

0.22 lb (100 g) can

(A dosage spoon is available free of charge. One spoon equals 0.02 lb (10 g) of enzyme granulate.)

HS Customs Tariff: 3507 90 90

Certified Quality

Panzym Extract G enzyme is regularly tested for uniform high product quality during the production process. These tests include comprehensive technical function criteria as well as safeness according to food product laws. Furthermore, stringent inspections are performed immediately prior to and during final packaging.

Panzym Extract G enzyme complies with the purity criteria of the international code for wine treatment products and the provisions of German wine regulations.

Panzym® is a registered trademark of Novozymes A/S.

North America - HQ

44 Apple Street,
Tinton Falls, NJ 07724
Toll Free: 800 656-3344
(North America Only)
Voice: +1 732 212-4700

Europe/Africa/Middle East

Auf der Heide 2
53947 Nettersheim, Germany
Voice: +49 2486 809-0

Internormen Product Line

Friedensstraße 41
68804 Altlussheim, Germany
Voice: +49 6205 2094-0

Begerow Product Line

An den Nahewiesen 24
55450 Langenlonsheim, Germany
Voice: +49 6704 204-0

Brazil

Av. Julia Gaioli, 474 - Bonsucesso
07251-500 - Guarulhos
Brazil
Voice: +55 11 2465 8822

China

No. 7 Lane 280 Linhong Road,
Changning District,
Shanghai 200335, China
Voice: +86 21 5200 0422

Singapore

4 Loyang Lane #04-01/02
Singapore 508914
Voice: +65 6825 1668

For more information, please e-mail us at filtration@eaton.com or visit us online at eaton.com/filtration for a complete list of Eaton's filtration products.

Not all products in Eaton's Begerow Product Line are available in all regions. Please contact your local Eaton Filtration office to determine availability.

© 2013 Eaton Corporation. All Rights Reserved. All trademarks and registered trademarks are the property of their respective owners.

All information and recommendations appearing in this brochure concerning the use of products described herein are based on tests believed to be reliable. However, it is the user's responsibility to determine the suitability for his own use of such products. Since the actual use by others is beyond our control, no guarantee, expressed or implied, is made by Eaton as to the effects of such use or the results to be obtained. Eaton assumes no liability arising out of the use by others of such products. Nor is the information herein to be construed as absolutely complete, since additional information may be necessary or desirable when particular or exceptional conditions or circumstances exist or because of applicable laws or government regulations.



Powering Business Worldwide